L2 / 24Port Network Switch – PoE 24 / 4SFP 10G

GT-Wave

GA24P-4S10G-LM



Supports HiPoE
Port 1~2 / 90W

Features

- 10/100/1000Mbps, **Ethernet 24port + 10Gbps SFP 4port**
- **Supports optical port ring configuration.**
- **Supports Ethernet port ring configuration.**
- **Web managed**

Item		Specification
PoE Port		**24 x 1Gbps**
Up-link	Ethernet	24 x 1Gbps (Users can choose whether to use POE or not)
	SFP	**4 x 10Gbps**
PoE standard		IEEE802.3 af/at /PoE+/BT (Class8) **Port 1~2 : BT supports (MAX 90W)** / Port3~24 (MAX 30W)
Input power / Capacity		AC 220V / 400Watt
CPU/ Meorry/ Flash		400MHz / ARM Core9 / 2G DDR / 64M Flash
Buffer		12M
Bandwidth		256Gbps
Packet forwarding		92.32Mpps
MAC Address		16K
Network Protocol		IEE802.3/ IEE802.3u 100BASE-TX /IEE802.3ab 1000BASE-TX /IEE802.3x /IEEE802.3ad / IEEE802.3z 1000BASE-X / IEEE802.3q /IEEE802.3q/p /IEEE802.1w /IEEE802.1d/ IEEE802.1S /STP/ RSTP (Rapid Spanning Tree Protocol) /MSTP
Port Configuration		flow control, mirroring, aggregation, isolation , ACL
VLAN		4094 VLAN addresses, MTU VLAN
STP function		STP/RSTP/MSTP
IGMP		IGMP snooping V1 / V2 / V3
PoE control		Auto-recovery for communication failure / Monitoring the status of each port
Lighting protection		5KV 8/20us
Transmission Mode		Store and Forward(full wirespeed)
Dimension / Weight		440 x 290 x 45 mm / 3.5Kg
Temperature		operating temperature -20℃~60℃

